



## MODELS 2015 & 2016 AUTOMATIC STOP

Features an easy to set, five digit, touch control electronic counter with large digital readout. Preset counter to number of turns required. The winder will stop instantly when preset number is reached. Release foot pedal and press reset.. The winder is ready for the next coil.

For operator safety, in case of emergency, the winder will stop instantly when the foot pedal is released. The foot pedal has a long cord for convenient positioning. It utilizes a heavy-duty spur drive gearbox, engineered for extra heavy-duty applications requiring exceptional pulling power.

All controls and speed adjustments are at the operator's fingertips on the front of the winder. Requires air to operate the brake & clutch, 70-PSI pressure and 5.0 cu. in. Consumption to operate.

manual models.

## SPECIFICATIONS

**Capacity:** Maximum torque: fast speed, 77 ft.-lbs; slow speed, 770 ft.-lbs.

**Dimensions:** 19" x 20 3/4" base, 47 3/4" height. Shaft Center height 42 1/2".

**Face Plate Shaft:** Tapped to take a standard 1/2" - 13 bolt for quick set-up in winding solenoid, electromagnet, and other small wound coils.

**AT LAYCOCK, WE MAKE WINDING EASIER!  
LAYCOCK KEEPS ONE STEP AHEAD!**

QUESTIONS OR COMMENTS? EMAIL US AT [laysys@verizon.net](mailto:laysys@verizon.net)